

FORM COAT-O

DESCRIPTION

FORM COAT-O is a lightly reactive form release in a hydrocarbon carrier. It is water insoluble, containing no paraffin or silicone.

FEATURES

★ Improved release from formwork ★ No residue ★ Cost effective ★ Prolongs life of forms

PREPARATION

Formwork surfaces should be clean and dry before applying FORM COAT-O. For best results, remove any dirt, rust, scale or concrete before application. Formwork that has been previously treated with a neutral form release should be cleaned with detergent and warm water, then thoroughly rinsed and dried before using FORM COAT-O.

APPLICATION

Apply FORM COAT-O per recommended rates below with a brush, roller, or sprayer. Spray application is recommended. Wipe off excess and drips with a clean, soft rag. Allow product to dry for at least 30 minutes before pouring concrete. New wood forms will require at least one "primer" coat of Form Coat-O. Apply the "primer" coat at the recommended rate below and allow it to absorb into the surface and dry for 30 minutes. A second "primer" coat may be necessary if the wood is extremely absorbent. After "priming", recoat and allow it to dry for 30 minutes. Wipe off any excess or drips before pouring concrete.

NET COVERAGE RATE

Steel, Plastic:	1500 ft ² per gallon	BB Grade Plyform:	800 ft ² per gallon
MDO Plywood:	1200 ft ² per gallon	Dimensional Lumber:	800 ft ² per gallon

TECHNICAL DATA

VOC: <100g/L

Flash Point: 105°F

HMIS

Health 2 Flammability 2

Reactivity 0 Protection B

CLEANUP

Clean tools with solvent

DISCLAIMER: Since manufacturer has no control over handling, use or storage; no guarantee expressed or implied, is offered. Clemons Concrete Coatings warrants the product to be free of defects and will replace or refund the purchase price of said products proven defective. Labor cost and/or other consequential damages are not covered by this warranty. Responsibility for claims of any kind is strictly limited to the purchase price of the product. The suitability of the product for any extended use shall be solely up to the user.

Made in USA

CLEMONS CONCRETE COATINGS

505 Cave Road Nashville TN 37210 ★ www.ccc-usa.com ★ Tel: 615-872-9099 ★ Fax: 615-872-9052